###ÿÿÿÿ###################################(###Û#######P#r#o#p#e#r#t#i#e#s#########
#######################################ÿÿÿÿÿÿÿÿÿÿÿÿÿ##############################
#####,###O#######Ý#1#×#F#Ã#Ã#Ï#T#Ñ#Ä#C#Ì#Y#P#Î#Ï#T#0#È#Í#Ð#A#=#=################2#
##ÿÿÿÿÿÿÿÿ#######################
pLnH]Ö#ÀöMnH]Ö############I#t#e#m###
########
###ÿÿÿÿ####ÿÿÿÿ###################################Õ####
%######P#r#o#p#e#r#t#i#e#s##ÿÿÿÿÿÿÿÿ
ÿÿÿÿ###################################2###@#######<?xml version="1.0"
encoding="utf-8"?><LongProperties
xmlns="http://schemas.microsoft.com/office/2006/metadata/longProperties"/><?xml
version="1.0" encoding="UTF-8" standalone="no"?>
<ds:datastoreItem ds:itemID="{C1CE732F-C316-416E-BFE9-2A12D7F20710}"
xmlns:ds="http://schemas.openxmlformats.org/officeDocument/2006/customXml"><ds:schemaRefs><ds:schemaRef
ds:uri="http://schemas.microsoft.com/office/2006/metadata/longProperties"/></
ds:schemaRefs></ds:datastoreItem>###<?
mso-contentType?><spe:Receivers xmlns:spe="http://schemas.microsoft.com/sharepoint/
events"><Receiver><Name>Document ID
Generator</Name><Synchronization>Synchronous</Synchronization><Type>10001</
Type><SequenceNumber>1000</
SequenceNumber><Assembly>Microsoft.Office.DocumentManagement, Version=14.0.0.0,
Culture=neutral,
PublicKeyToken=71e9bce111e9429c</Assembly><Class>Microsoft.Office.DocumentManagement.Internal.DocIdHandler</Class><Data></Data><Filter></Filter></
Receiver><Receiver><Name>Document ID Generator</Name><Synchronization>Synchronous</
Synchronization><Type>10002</Type><SequenceNumber>1001</
SequenceNumber><Assembly>Microsoft.Office.DocumentManagement, Version=14.0.0.0,
Culture=neutral,
PublicKeyToken=71e9bce111e9429c</Assembly><Class>Microsoft.Office.DocumentManagement.Internal.DocIdHandler</Class><Data></Data><Filter></Filter></
Receiver><Receiver><Name>Document ID Generator</Name><Synchronization>Synchronous</
Synchronization><Type>10004</Type><SequenceNumber>1002</
SequenceNumber><Assembly>Microsoft.Office.DocumentManagement, Version=14.0.0.0,
Culture=neutral,
PublicKeyToken=71e9bce111e9429c</Assembly><Class>Microsoft.Office.DocumentManagement.Internal.DocIdHandler</Class><Data></Data><Filter></Filter></
Receiver><Receiver><Name>Document ID Generator</Name><Synchronization>Synchronous</
Synchronization><Type>10006</Type><SequenceNumber>1003</
SequenceNumber><Assembly>Microsoft.Office.DocumentManagement, Version=14.0.0.0,
Culture=neutral,
PublicKeyToken=71e9bce111e9429c</Assembly><Class>Microsoft.Office.DocumentManagement.Internal.DocIdHandler</Class><Data></Data><Filter></Filter></Receiver></
spe:Receivers>##########################<?xml version="1.0" encoding="UTF-8"
standalone="no"?>
<ds:datastoreItem ds:itemID="{CB229A47-22E7-49F7-8ACB-E6142143127C}"
xmlns:ds="http://schemas.openxmlformats.org/officeDocument/2006/customXml"><ds:schemaRefs><ds:schemaRef
ds:uri="http://schemas.microsoft.com/sharepoint/events"/></ds:schemaRefs></
ds:datastoreItem>##<?
mso-contentType?><FormTemplates
xmlns="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms"><Display>DocumentLibraryForm</Display><Edit>DocumentLibraryForm</Edit><New>DocumentLibraryForm</
New></FormTemplates>####################################<?xml version="1.0"
encoding="UTF-8" standalone="no"?>
<ds:datastoreItem ds:itemID="{472C14B4-84D1-4B8B-86FB-85EAC90C9E6C}"
xmlns:ds="http://schemas.openxmlformats.org/officeDocument/2006/customXml"><ds:schemaRefs><ds:schemaRef
ds:uri="http://schemas.microsoft.com/sharepoint/v3/contenttype/forms"/></

ds:schemaRefs></
ds:datastoreItem>##<?xml
version="1.0" encoding="UTF-8" standalone="no"?>
<ds:datastoreItem ds:itemID="{8EC5BDF5-D33B-40C6-AC60-FBAF4DAA2DC0}"
xmlns:ds="http://schemas.openxmlformats.org/officeDocument/2006/customXml"><ds:sche
maRefs><ds:schemaRef
ds:uri="http://schemas.microsoft.com/office/2006/metadata/contentType"/
><ds:schemaRef
ds:uri="http://schemas.microsoft.com/office/2006/metadata/properties/<?xml
version="1.0" encoding="utf-8"?><ct:contentTypeSchema ct:_="" ma:_=""
ma:contentTypeName="Document"
ma:contentTypeID="0x01010077E8F708C843AB40A5A0D58C9AD21769"
ma:contentTypeVersion="0" ma:contentTypeDescription="Create a new document."
ma:contentTypeScope="" ma:versionID="451b84111a2b33a3123f02a69e79d924"
xmlns:ct="http://schemas.microsoft.com/office/2006/metadata/contentType"
xmlns:ma="http://schemas.microsoft.com/office/2006/metadata/properties/
metaAttributes">
<xsd:schema targetNamespace="http://schemas.microsoft.com/office/2006/metadata/
properties" ma:root="true" ma:fieldsID="d6cf115dc1f6827e14f844cccabb302f" ns2:_=""
xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:p="http://schemas.microsoft.com/office/2006/metadata/properties"
xmlns:ns2="f678b3e7-99ca-49a2-9591-16a4ba76fdac">
<xsd:import namespace="f678b3e7-99ca-49a2-9591-16a4ba76fdac"/>
<xsd:element name="properties">
<xsd:complexType>
<xsd:sequence>
<xsd:element name="documentManagement">
<xsd:complexType>
<xsd:all>
<xsd:element ref="ns2:_dlc_DocId" minOccurs="0"/>
<xsd:element ref="ns2:_dlc_DocIdUrl" minOccurs="0"/>
<xsd:element ref="ns2:_dlc_DocIdPersistId" minOccurs="0"/>
<xsd:element ref="ns2:Display_x0020_In_x0020_Nav" minOccurs="0"/>
<xsd:element ref="ns2:Page_x0020_Display_x0020_Order" minOccurs="0"/>
</xsd:all>
</xsd:complexType>
</xsd:element>
</xsd:sequence>
</xsd:complexType>
</xsd:element>
</xsd:schema>
<xsd:schema targetNamespace="f678b3e7-99ca-49a2-9591-16a4ba76fdac"
elementFormDefault="qualified" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xs="http://www.w3.org/2001/XMLSchema"
xmlns:dms="http://schemas.microsoft.com/office/2006/documentManagement/types"
xmlns:pc="http://schemas.microsoft.com/office/infopath/2007/PartnerControls">
<xsd:import namespace="http://schemas.microsoft.com/office/2006/documentManagement/
types"/>
<xsd:import
namespace="http://schemas.microsoft.com/office/infopath/2007/PartnerControls"/>
<xsd:element name="_dlc_DocId" ma:index="8" nillable="true"
ma:displayName="Document ID Value" ma:description="The value of the document ID
assigned to this item." ma:internalName="_dlc_DocId" ma:readOnly="true">
<xsd:simpleType>
<xsd:restriction base="dms:Text"/>
</xsd:simpleType>
</xsd:element>
<xsd:element name="_dlc_DocIdUrl" ma:index="9" nillable="true"

```
ma:displayName="Document ID" ma:description="Permanent link to this document."
ma:hidden="true" ma:internalName="_dlc_DocIdUrl" ma:readOnly="true">
<xsd:complexType>
<xsd:complexContent>
<xsd:extension base="dms:URL">
<xsd:sequence>
<xsd:element name="Url" type="dms:ValidUrl" minOccurs="0" nillable="true"/>
<xsd:element name="Description" type="xsd:string" nillable="true"/>
</xsd:sequence>
</xsd:extension>
</xsd:complexContent>
</xsd:complexType>
</xsd:element>
<xsd:element name="_dlc_DocIdPersistId" ma:index="10" nillable="true"
ma:displayName="Persist ID" ma:description="Keep ID on add." ma:hidden="true"
ma:internalName="_dlc_DocIdPersistId" ma:readOnly="true">
<xsd:simpleType>
<xsd:restriction base="dms:Boolean"/>
</xsd:simpleType>
</xsd:element>
<xsd:element name="Display_x0020_In_x0020_Nav" ma:index="11" nillable="true"
ma:displayName="Display In Nav" ma:default="1" ma:description="Use this value to
determine whether a link or page is currently visible in the Navigation control."
ma:internalName="Display_x0020_In_x0020_Nav">
<xsd:simpleType>
<xsd:restriction base="dms:Boolean"/>
</xsd:simpleType>
</xsd:element>
<xsd:element name="Page_x0020_Display_x0020_Order" ma:index="12" nillable="true"
ma:displayName="Page Display Order" ma:decimals="0" ma:default="1"
ma:description="Use this property to control the order that pages will display
within the Navigaton control." ma:internalName="Page_x0020_Display_x0020_Order"
ma:readOnly="false" ma:percentage="FALSE">
<xsd:simpleType>
<xsd:restriction base="dms:Number">
<xsd:maxInclusive value="1000000"/>
<xsd:minInclusive value="1"/>
</xsd:restriction>
</xsd:simpleType>
</xsd:element>
</xsd:schema>
<xsd:schema
targetNamespace="http://schemas.openxmlformats.org/package/2006/metadata/core-
properties" elementFormDefault="qualified" attributeFormDefault="unqualified"
blockDefault="#all" xmlns="http://schemas.openxmlformats.org/package/2006/metadata/
core-properties" xmlns:xsd="http://www.w3.org/2001/XMLSchema"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance" xmlns:dc="http://purl.org/dc/
elements/1.1/" xmlns:dcterms="http://purl.org/dc/terms/"
xmlns:odoc="http://schemas.microsoft.com/internal/obd">
<xsd:import namespace="http://purl.org/dc/elements/1.1/"
schemaLocation="http://dublincore.org/schemas/xmls/qdc/2003/04/02/dc.xsd"/>
<xsd:import namespace="http://purl.org/dc/terms/"
schemaLocation="http://dublincore.org/schemas/xmls/qdc/2003/04/02/dcterms.xsd"/>
<xsd:element name="coreProperties" type="CT_coreProperties"/>
<xsd:complexType name="CT_coreProperties">
<xsd:all>
<xsd:element ref="dc:creator" minOccurs="0" maxOccurs="1"/>
<xsd:element ref="dcterms:created" minOccurs="0" maxOccurs="1"/>
<xsd:element ref="dc:identifier" minOccurs="0" maxOccurs="1"/>
```

```
<xsd:element name="contentType" minOccurs="0" maxOccurs="1" type="xsd:string"
ma:index="0" ma:displayName="Content Type"/>
<xsd:element ref="dc:title" minOccurs="0" maxOccurs="1" ma:index="4"
ma:displayName="Title"/>
<xsd:element ref="dc:subject" minOccurs="0" maxOccurs="1"/>
<xsd:element ref="dc:description" minOccurs="0" maxOccurs="1"/>
<xsd:element name="keywords" minOccurs="0" maxOccurs="1" type="xsd:string"/>
<xsd:element ref="dc:language" minOccurs="0" maxOccurs="1"/>
<xsd:element name="category" minOccurs="0" maxOccurs="1" type="xsd:string"/>
<xsd:element name="version" minOccurs="0" maxOccurs="1" type="xsd:string"/>
<xsd:element name="revision" minOccurs="0" maxOccurs="1" type="xsd:string">
<xsd:annotation>
<xsd:documentation>
                        This value indicates the number of saves or revisions. The
application is responsible for updating this value after each revision.
                    </xsd:documentation>
</xsd:annotation>
</xsd:element>
<xsd:element name="lastModifiedBy" minOccurs="0" maxOccurs="1" type="xsd:string"/>
<xsd:element ref="dcterms:modified" minOccurs="0" maxOccurs="1"/>
<xsd:element name="contentStatus" minOccurs="0" maxOccurs="1" type="xsd:string"/>
</xsd:all>
</xsd:complexType>
</xsd:schema>
<xs:schema targetNamespace="http://schemas.microsoft.com/office/infopath/2007/
PartnerControls" elementFormDefault="qualified" attributeFormDefault="unqualified"
xmlns:pc="http://schemas.microsoft.com/office/infopath/2007/PartnerControls"
xmlns:xs="http://www.w3.org/2001/XMLSchema">
<xs:element name="Person">
<xs:complexType>
<xs:sequence>
<xs:element ref="pc:DisplayName" minOccurs="0"></xs:element>
<xs:element ref="pc:AccountId" minOccurs="0"></xs:element>
<xs:element ref="pc:AccountType" minOccurs="0"></xs:element>
</xs:sequence>
</xs:complexType>
</xs:element>
<xs:element name="DisplayName" type="xs:string"></xs:element>
<xs:element name="AccountId" type="xs:string"></xs:element>
<xs:element name="AccountType" type="xs:string"></xs:element>
<xs:element name="BDCAssociatedEntity">
<xs:complexType>
<xs:sequence>
<xs:element ref="pc:BDCEntity" minOccurs="0" maxOccurs="unbounded"></xs:element>
</xs:sequence>
<xs:attribute ref="pc:EntityNamespace"></xs:attribute>
<xs:attribute ref="pc:EntityName"></xs:attribute>
<xs:attribute ref="pc:SystemInstanceName"></xs:attribute>
<xs:attribute ref="pc:AssociationName"></xs:attribute>
</xs:complexType>
</xs:element>
<xs:attribute name="EntityNamespace" type="xs:string"></xs:attribute>
<xs:attribute name="EntityName" type="xs:string"></xs:attribute>
<xs:attribute name="SystemInstanceName" type="xs:string"></xs:attribute>
<xs:attribute name="AssociationName" type="xs:string"></xs:attribute>
<xs:element name="BDCEntity">
<xs:complexType>
<xs:sequence>
<xs:element ref="pc:EntityDisplayName" minOccurs="0"></xs:element>
```

```
########ð####`#▫###@####ðH#######$#####ñ###############################¯ç##Ã#####ÿÿ
ÿÿ#################ðv#####▫###########¨#,###Prefer to see information such as
pictures, diagrams, cartoons, demonstrationsPicture words and concepts they hear as
imagesEasily distracted in lecture with no visual aidsOverwhelmed with intense
visuals accompanied by lectureBenefit from using charts, maps, notes, and flash
cards when studying##¡#####-#########-#####C#########ª#####-#########  #
      ####ð▫###²#
ð#####,###
##▫##ðB###▫#▫#á##A##########?#####¿#####ÿ#####▫Ã####¿#####O#b#j#e#c#t#
#4#####"ñÎ###©ÃÈ###PK##########!#ÛáöËî###▫#######[Content_Types].xml|▫ÏNÃ0
```

```
####¯ç##Ã#####ÿÿÿÿ##################ðx#####▫###########¨#º###Extroverts Like
talking with others and taking action.Prefer active learning and group projects.
IntrovertsPrefer to have others do the talking.Prefer lectures and structured
tasks.##¡#▫###
```

#####ðå#####▫###########¨#{###Different instructors have different goals regarding student participation. Some expect students to concentrate on listening, thinking, and taking notes. Others want you to be actively involved in other ways as well. Participating in various ways will develop your academic skills. Asking or responding to questions can make a class more worthwhile for you and your classmates. ##¡#$###{#######
###h###########
###|#########ª#####|######### #   ###¦#

```
###############################################################"#######Calibri#####
Arial#####Calibri Light#####Times New Roman#####Tahoma#####Impact#####Baskerville
Old Face#####Sylfaen#####TRENDY#
###Wingdings#####Verdana#####MS Pã□´ã□·ã□□ã□¯#####Harrington#####Arial Unicode
MS#####Retrospect####1_Retrospect####2_Retrospect####3_Retrospect####4_Retrospect#
###5_Retrospect####6_Retrospect#####Clip#####What are Learning Styles?#####Visual
Learners#####Auditory Learners# ###Tactile or Kinesthetic Learners#5###Your
Intelligence Profile created by Howard Gardner #/###Extraversion/Introversion
(Social Orientation)#####Thinking/Feeling (Decision Making)#%###Judging/Perceiving
(Achieving Goals)#%###Discovering Your  Own Learning Style#'###Using Knowledge of
Your Learning Style#+###Build Strengths across the Learning Styles#J###Remember! No
matter what your Learning Style is itâ□□s very important to-#
```

```
###############Fonts Used#################Theme#################Embedded OLE
Servers################Slide Titles#####
```